



SECCION RECOMENDADA
6 mm²

P
1500 RPM

TENSION LINEA POWER DN PRESENCE SELECTEUR | MANDO MOTOR MOTOR COMANDE COMMANDE MOTEUR | BAJADA PUNZON PUNCH DOWN DESCENTE POINCON | SUBIDA PUNZON PUNCH UP MONTÉE POINCON | SUBIDA CHAPA SHEAR UP MONTÉE CISAILLE | BAJADA CHAPA AUTOM. SHEAR AUTOM. SHEAR BOTTON DESCENTE CISAILLE | BAJADA CHAPA AUTOM. SHEAR AUTOM. SHEAR BOTTON DESCENTE CISAILLE AUTOM.

HYD 55 A (50 Hz)

HYD 80 - 110 A (50 Hz)
HYD 55-80-110 A (60 Hz)

	220 V	380-415 V
QS	25 A	25 A
QM	QM2 9-14 A	QM1 6-10 A
KM	KM1	KM
s	2,5	2,5
P	3 KW	

	220 V	380-415 V
QS	25 A	25 A
QM	QM4 17-23 A	QM2 9-14 A
KM	KM2	KM1
s	4	2,5
P	5,5 KW	

G.	-				
F.	-				
E.	-	Dibujado	MARTIN	<i>Maquinaria GEKA, S.A.</i>	
D.	-	Comprobado	25-5-05		
C.	-	Escala	HYD 55-80-110 A-AD (220-380-415 V)	N° Plano	
B.	-	Fecha	ESQUEMA ELECTRICO	2131	
A.	-				
S.	-				